



trivum Digital Input trivum Analog Input

The trivum Digital Input adapter convert in a simple way optical TOSLINK sources to the trivum Audiobus.

The trivum Analog Input adapter uses a 3,5mm (1/8 inch) TRS for it's input. So it is flexible for daily application.

The trivum Audiobus is our special bus for audio sources. It's designed for high quality audio connections and to avoid interference.



Digital Input adapter TOSLINK



Analog Input adapter 3,5mm (mini) jack



Digital Input adapter Audiobus



trivum technologies GmbH Heusteigstrasse 37 70180 Stuttgart Telefon: +49 711 64 56 07-10 Telefax: +49 711 64 56 07-16 info@trivum.com

10110

Analog Input

Digital Input

With the analog input connection you can connect fast and simple a wide range of analog sources.

With the optical TOSLINK connection you can connect

high-grade cd player, TV, video game consoles and

many more devices to your trivum multiroom system.

Bus powered



Our trivum Audiobus supply the power for the adapters. So you don't need any external power supply. That makes installation more easy with less wiring.

trivum Audiobus To connect to a trivum system, we use our trivum

Audiobus. With a shielded CAT5 cable you don't need any special wiring. With it's symmetrical routing, it avoid interference for a high quality audio connection.





trivum **Digital Input** trivum **Analog Input**

Specification:



Connections:	Digital Input adapter:
	Input optical TOSLINK, Output RJ45 (trivum Audiobus).
	Analog Input adapter:
	Input 3,5mm (mini) jack, Output RJ45 (trivum Audiobus).
Funktion:	Digital Input adapter:
	Convert digital audio sources to symmetrical trivum Audiobus.
	Support audio-sampling rates up to 96kHz / 24bit.
	Support mixdown from 5.1 channel-audio to 2 channel-audio.
	Analog Input adapter:
	Convert analog sources to symmetrical trivum Audiobus.
Compatibility:	AudioAktor 4x, C4 Input Connect, C4 Speaker Connect, C4 PowerAmp Connect
Please Note:	The trivum Audiobus wiring must be a point-to-point connection between the adapter and
	the trivum system. You must use a shielded CAT5 cable.
	Router/Switches are not supportet.
	The adapter is trivum powered via the CAT5 cable. Please do not connect other devices,
	as they can be damaged.
Power:	No external power supply needed.
	The adapter is bus powered from trivum AudioAktor 4x and trivum C4.
Dimension:	70mm x 25mm x 37mm (WxHxD)

The focus of trivum's development lies on KNX and music. The trivum Multiroom System offers the highest possible degree of functionality and quality in an intelligent control. Special features of all trivum products are the simplicity and the flexibility combined with the possibility of integration in KNX surroundings. The spectrum of possible trivum solutions involves single rooms (like e.g. music for the kitchen) or even networks your complete home with music. For more information please visit www.trivum.de.



trivum technologies GmbH Heusteigstrasse 37 70180 Stuttgart phone: +49 711 64 56 07-10 fax: +49 711 64 56 07-16 info@trivum.com