




SMART CONNECT KNX Loewe

Product	Order number	VE	PP
 SMART CONNECT KNX Loewe DRA, TP1	1-000B-009	1	1

Technical data

Rated voltage:	DC 24 V to 30 V
Power consumption:	2 W (24 V DC external supply)
Ambient temperature:	0 °C to +45 °C
KNX communication:	KNX/TP, S-Mode
KNX medium:	TP1-256
IP communication:	Ethernet 10/100 BaseT
Connections:	2x RJ45 (integrated switch) Connection and branching terminals for KNX and 24 V
Dimensions:	2 HP (DRA plus)

Information

Up to two Loewe televisions can be integrated via the gateway SMART CONNECT KNX Loewe into the KNX and adapted completely to meet your own requirements.

Features:

- Separate control of up to two televisions
- Television on/off
- Sound on/off
- Volume control
- Programme control
- PIP on/off
- Source selection
- Child protection on/off or age-dependently
- OSD text with pre-defined text (ETS) or from KNX (14 bytes)
- Simple integration into KNX (can be completely configured via ETS)
- Extensions via firmware updates
- Transfer camera images, e.g. from an external camera
- Open web pages via KNX, e.g. weather, news or from the camera
- Remote control key codes can be sent
- In addition to the IP address, the identification of the TV sets can also be made via the host name

Supports Loewe TV devices in chassis generations SL3xx/SL4xx.

The product may slightly differ from the illustration.

19.06.2023

**ise Individuelle Software
und Elektronik GmbH**
Osterstraße 15
26122 Oldenburg
Germany

Phone: +49 441-680 06-11
Fax: +49 441-680 06-15
E-mail: sales@ise.de
Web: www.ise.de