Data Sheet









SMART APP KNX Axis

Product	Order number	VE	PP	
SMART APP KNX Axis	A-0001-008 A-0001-019 A-0001-020	Single licence 5 volume licence 10 volume licence	2	

Technical data

KNX communication: KNX/IP (Routing), S-Mode

Information

Building automation and security technology combined flawlessly:

The world's first KNX connection (plug-in) for networking products from the Axis Communications company.

Note:

The plug-in can only be used on network devices from Axis Communications with ACAP support.

Features:

- Support of Axis network cameras
- Support of Axis WLAN cameras *
- Support of Axis D2050 -VE Network Radar Detector
- Support of Axis door stations
- Support of Axis network loudspeakers
- 30 group objects for sending from KNX to the Axis camera (1 bit)
- 30 group objects for sending from the Axis camera to KNX (variable bit length)
- · Control of actions on the camera
- Triggering of image, video and/or camera message sending
- With PTZ cameras, predefined positions can be focused on
- Camera settings (properties) can be read out and sent to the KNX
- Sending of a message to the KNX with access to the camera's live stream
- Monitoring of the camera itself, e.g. for overheating or breaking of the connection to the saving location for videos

Osterstraße 15 26122 Oldenburg

Germany

- Third-party applications can send values to the KNX
- Simple integration into KNX (can be completely configured via ETS and the camera's event system)

^{*} Only in combination with other system components that support reliable communication, e.g. Gira KNX/IP Router.