Datasheet **trivum M2**

trivum



Item No.	**201027**
EAN	**4260393851078**
HS Code	**85 198 100**
Product URL	https://www.trivum.com/en/m2
Release Date	October 2026

Amplifier	• 4x 125 W RMS into 4 ohms • Class-D amplifier (digital) • Minimum speaker impedance: 4 ohms
Power Supply	• 100-240 V AC (max. 600 W) • Idle power consumption (no active zone): approx. 5 W
Housing	• Black powder-coated sheet steel • Device: 216 x 71 x 232 mm (W x H x D) • Packaged: 322 x 77 x 293 mm (W x H x D) • Net weight: 2.55 kg
Connections	• 1x Network (RJ45) • 1x USB (service) • 2x Stereo speaker outputs (2x 2-pin terminal) • 1x Analog/digital stereo output (combo jack TOSLINK/3.5 mm) • 1x Analog/digital stereo input (combo jack TOSLINK/3.5 mm) • 1x Wi-Fi/Bluetooth antenna (SMA • 2x USB-C trivum Matrix input (SDAT/MDAT) • 2x USB-C trivum Matrix output (MDAT) • 1x Power (IEC 60320 C6)
Network	• LAN (RJ45 Ethernet) • Wi-Fi
Package Contents	• 1x M2 • 1x Wi-Fi antenna • 1x Power cord • 2x Pluggable speaker terminal blocks • 2x TOSLINK to combo jack adapters • 1x Quick Installation Guide

Specifications are subject to change without notice.

© trivum technologies GmbH - 2026
Eierstr. 48 - 70469 Stuttgart
www.trivum.com